



# KF-221FX Ver.C



## 100Base-FX Fast Ethernet PCI Adapter

### Ordering Informations:

Model	Fiber Mode	Connector	Ref. Distance
KF-221FX-T	MM	Dual ST	2km
KF-221FX-C	MM	Dual SC	2km
KF-221FX-JM	MM	MT-RJ	2km
KF-221FX-VM	MM	VF-45	2km
KF-221FX-SA2	SM	Dual SC	20km
KF-221FX-SL2	SM	Dual SC	20km
KF-221FX-SL3	SM	Dual SC	30km
KF-221FX-SL4	SM	Dual SC	40km
KF-221FX-W3515	SM	Bi-Di SC	15-20km
KF-221FX-W5315	SM	Bi-Di SC	15-20km

MM: Multimode Fiber  
 SM: Single Mode Fiber  
 Ref. Distance: Reference connection distance

### Key Features:

- PCI revision 2.1 and 2.2 compliance
- 32-bit PCI half-card supports standard PCI
- Supports 100Base-FX fiber connection
- Complies with IEEE 802.3u 100Base-FX standard
- Supports diversified fiber connectors
- Far End Fault support on the 100Base-FX port
- Wake-On-LAN (WOL) function for ACPI-compliant systems
- Supports plug-and-play installation for Windows XP/2000/ME/2003 systems
- Supports network drivers for most popular operating systems
- Optional PXE/RPL Boot ROM for network operating systems

### Specifications:

Fiber Connectors	MM: ST, SC, MT-RJ, VF-45, LC & SM: SC
LEDs	100M Link, Act, Duplex
ACPI std.	Rev.1.1
PCI Power Management	Rev.1.1
DMI	Ver.2.0
PXE/RPL	PXE Ver.2.1
Environment	Operation Temperature: 0°C ~ 40°C Relative Humidity: 10% ~ 90% non-condensing
Dimension	130 x 65 mm

### Fiber Optical Specifications:

Model	Connector	Fiber & Cable	Wavelength	Tx Power	Rx Sens.	Rx Max.
-T	ST Duplex	MMF	1310nm	-19 ~ -14dBm	-31dBm	-14dBm
-C	SC Duplex	MMF	1310nm	-19 ~ -14dBm	-31dBm	-14dBm
-JM	MT-RJ	MMF	1310nm	-19 ~ -14dBm	-31dBm	-14dBm
-VM	VF-45	MMF	1310nm	-20 ~ -14dBm	-31dBm	-14dBm
-SA2	SC Duplex	SMF	1310nm	-15 ~ -8dBm	-31dBm	-7dBm
-SL2	SC Duplex	SMF	1310nm	-15 ~ -7dBm	-32dBm	-3dBm
-SL3	SC Duplex	SMF	1310nm	-15 ~ -8dBm	-34dBm	0dBm
-SL4	SC Duplex	SMF	1310nm	-5 ~ 0dBm	-34dBm	-3dBm
-W3515	Bi-Di SC	SMF	TX 1310nm RX 1550nm	-14 ~ -8dBm	-31dBm	0dBm
-W5315	Bi-Di SC	SMF	TX 1550nm RX 1310nm	-14 ~ -8dBm	-31dBm	0dBm

MMF : Multimode fiber -62.5/125 μm,50/125 μm  
 SMF : Single Mode fiber -9 /125 μm



FCC Part 15, Class B  
 CISPR 22 Class B

### Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,  
 Hsi-chih, Taipei Hsien, Taiwan.  
 Tel: 886-2-2698-3878  
 Fax: 886-2-2698-3873  
 E-mail: kti@ktinet.com.tw  
 URL: http://www.ktinet.com.tw

### KTI Networks Inc.

10415-A Westpark Drive, Houston,  
 TX 77042. U.S.A.  
 Tel: 1-713-266-3891  
 Fax: 1-713-914-0555  
 E-mail: contact@ktinet.com  
 URL: http://www.ktinet.com

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.  
 This information is subject to change without prior notice.