



KGC-261-DP/G



Industrial Media Converters with PoE++ PSE Support

Product Highlights:

- Tri-speed copper to dual-speed fiber conversion
- Advanced LFPT, OPA, ALS features
- PoE PSE functionality
- Support PoE++ 90W PD
- Web & SNMP management

DC Input:



Approval:

FCC Class A, VCCI Class A
 CE mark Class A
 LVD IEC60950-1 safety
 EN 55032 emission
 EN 55024 immunity
 IEC 60068-2-64 vibration
 IEC 60068-2-27 shock 30G test

Key Features:

- Industrial Media Converter with PoE++ PSE for general applications
- Tri-speed 10/100M/1Gbps copper to dual-speed 100M/1Gbps fiber conversion
- Comply with IEEE 802.3, 802.3u, 802.3ab, 802.3z, 802.3af, 802.3at standard
- Support full wire speed conversion for Gigabit copper to Gigabit fiber
- Provide dual-speed SFP on fiber port for mounting variety of fiber options
- Provide important LFPT (Link Fault Pass Through) media converter function
- Support Jumbo frame conversion
- Energy Efficient Ethernet (EEE) support
- Alarm events relay output
- Optical Power Alarm (OPA) function
- Auto Laser Shutdown (ALS) function
- Fiber support for multimode, short reach up to long reach single mode fiber, Bi-Di applications
- Web-based configuration management support
- Support SNMP management
- PoE PSE capability to support 802.3af PDs, 802.3at PDs and proprietary PoE++ 90W PDs
- PoE shutdown protection for non-compliant PD, disconnection, over-current and short-circuit


Specifications:

Standard	IEEE 802.3u, 802.3ab, 802.3z, 802.1ad, 802.3az, 802.1Q, 802.3af, 802.3at
Copper Port	Shielded RJ-45, 10/100/1000Mbps, Full/Half duplex Auto-negotiation, Auto-MDI/MDI-X
Fiber Port	SFP connector with pre-configured SFP fiber transceiver 100Mbps/1Gbps Full duplex, Auto-negotiation Far End Fault support
Network Cables	Copper port: Cat.5e recommended or higher up to 100m Fiber port: MMF 50/125µm, 62.5/125µm, SMF 9/125µm
LED Indication	Unit: power status, PoE status Per port: 1G/Link/Activity, 10-100/Link/Activity
Jumbo Frame size	Up to 9.6K bytes
DC TB Input	Flange terminal block: DC+/ DC-/ 3 Relay contacts Rated voltage range: +12 ~ +57VDC
Relay Output	3 dry contacts for NC & NO pairs on DC TB Contact rating: 30VDC/1A or 120VAC/0.5A Alarm events: power failure, configured port link fault, OPA
DC Jack Input	Power jack (Contacts: -D6.3mm, +D2.0mm) Rated voltage range: +12 ~ +48VDC




EMI EMS Safety Environmental Tests:

Test	Standard	Specifications
FCC/EMI	FCC Rule Part 15	Class A
CE/EMC/EMI	EN 55032	Class A
CE/EMC/EMS	EN 55024	
ESD Test	IEC 61000-4-2	Contact: +/-8kV Air: +/-15kV
RS Test	IEC 61000-4-3	Strength: 20V/m
EFT/BURST	IEC 61000-4-4	DC IN: +/-4kV RJ-45: +/-4kV
Surge Immunity	IEC 61000-4-5	DC IN: +/-1kV RJ-45: +/-4kV
CS Test	IEC 61000-4-6	Level 3
Magnetic Field Imm.	IEC 61000-4-8	50/60Hz, 100A/m, 60s 50/60Hz, 1000A/m, 1s
Safety	EN 60950-1	
Dielectric Voltage	IEEE 802.3	TP, 1500VAC/60sec.
Insulation Resistance	IEEE 802.3	TP, 500VDC/10Mohm
Cold Test	IEC 60068-2-1 Ad	-40°C, 72hrs
Dry Heat Test	IEC 60068-2-2 Bd	+75°C, 30%RH, 72hrs
Damp Heat Test	IEC 60068-2-3 Ca	+75°C, 95%RH, 72hrs
Storage Test	IEC 60068-2-48	-40°C, 96hrs +85°C, 30%RH, 96hrs
Vibration Test	IEC 60068-2-64 Fh	10~150Hz, 2.0 g/Hz
Shock Test	IEC 60068-2-27 Ea	30G



DIN-Rail Dimension



Panel Dimension



Katron Technologies Inc.
 15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
 Hsi-chih District, New Taipei City, Taiwan
 Tel: 886-2-2698-3878
 Fax: 886-2-2698-3873
 E-mail: kti@ktinet.com.tw
 URL: http://www.ktinet.com.tw

Trademarks: All brand names are trademarks or registered trademarks of their respective holders. This information is subject to change without prior notice.

DC DIN Input	Power DIN, Mini-DIN-4 socket Contact rating: 2.7A 48V Rated voltage range: +12 ~ +48VDC
DC Power	General: +12 ~ +57VDC PoE: +45 ~ +57VDC Polarity reversal protection
Power Consumption	Non PoE: 4W , PoE: 5W
Housing	Enclosed metal with no fan
Environment	Operating Temperature: -40°C ~ 75°C Storage Temperature: -40°C ~ 85°C Relative Humidity: 5% ~ 95% non-condensing
Dimension	40 x 106 x 140 mm (WxDxH)
Mounting Support	DIN-Rail, Panel (optional)
MTBF	250K hours min
Management:	
Management	Web-based browser interface, SNMP manager Port Control Operating mode, Flow control, LLDP, PoE control
Packet Filtering	802.1Q tagged packet filtering, Untagged packet filtering
802.1Q VLAN	Ingress 802.1Q tag stripping, Egress 802.1Q tagging (tag insertion) S-tag tagging (802.1ad double tagging)
Maintenance	Restore factory default, reboot, firmware update
SNMP	Trap events: Bootup, Login failure, Port link changes, OPA SNMP Private MIB: DDM, Remote boot, OPA, PoE

PSE Support:

PSE Output vs. PD Input

PD Type	Class	DC IN min.	PSE OUT	PD IN min.*2
1	0	45V	15.4W	12.95W
1	1	45V	4W	3.84W
1	2	45V	7W	6.49W
1	3	45V	15.4W	12.95W
2	4	51V	32W	25.5W
3*1	5	55V	50W	38.7W
3*1	6	55V	74W	52.7W
4*1	7	55V	90W	70W
4*1	8	55V	128W	90W

*1: PD Types & associated classes are proprietary PoE++ std.
 *2: The power received at PD in worst case

Fiber Optical Specifications:

1Gbps	Fiber Port	Wavelength	Tx Power*	Rx Sens.	Rx Max.	Distance*
-SX	LC 62.5/125 MMF 50/125 MMF	850nm	-9.5 ~ -4dBm	-18dBm	0Bm	220m 500m
-LX	LC MMF SMF	1310nm	-9.5 ~ -3dBm	-20dBm	-3dBm	550m 10km
-LX70	LC SMF	1550nm	0 ~ +5dBm	-24dBm	-3dBm	70km
-W3510	Bi-Di LC SMF	Tx 1310nm Rx 1550nm	-9 ~ -3dBm	-21dBm	-1dBm	10km
-W5310	Bi-Di LC SMF	Tx 1550nm Rx 1310nm	-9 ~ -3dBm	-21dBm	-1dBm	10km
100Mbps Fiber Port	Wavelength	Tx Power*	Rx Sens.	Rx Max.	Distance*	
-FM	LC MMF	1310nm	-20 ~ -14dBm	-31dBm	0dBm	2km
-FS30	LC SMF	1310nm	-15 ~ -8dBm	-34dBm	0dBm	30km

* Tx Power data for 62.5/125µm MMF, 9/125µm SMF
 Distance: reference connection distance