



KS-116, KS-124



16/24-Port 10/100 Workgroup Fast Ethernet Switches

Key Features:

- Provide 16/24 10/100Mbps Fast Ethernet ports
- All ports support auto-negotiation and auto-MDI/MDI-X detection
- Support full/half-duplex transfer mode for 10/100Mbps
- Wire speed reception and transmission
- Store-and-Forward switching method
- Self learning for active MAC addresses up to 8K entries
- Supports IEEE 802.3x flow control for full-duplex mode and backpressure flow control for half-duplex mode

Specifications:

Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX		
Number of Ports	16/24 x 10/100Mbps auto-negotiation & auto-MDI/MDI-X ports		
Network Ports	10Base-T:	Cat.3, 4, 5 or higher (100 meters max.)	
	100Base-TX:	Cat.5, 5e or higher (100 meters max.)	
Network Data Transfer Rate	Ethernet:	10Mbps (Half-duplex)	20Mbps (Full-duplex)
	Fast Ethernet:	100Mbps (Half-duplex)	200Mbps (Full-duplex)
MAC Address Table	8K entries		
LEDs	Per Unit: Power Per Port: Link/ACT, and speed		
Environment	Operating temperature: 0°C ~ 40°C Storage temperature: -20°C ~ 70°C Humidity: 10% ~ 90%RH non-condensing		
Dimension	283 x 178 x 45 mm (19" rack mountable)		
Power	100-240VAC, 50-60Hz		
Power Consumption	KS-116: 6 watts. (max.) KS-124: 6.4 watts. (max.)		
Approval	FCC Class A, CE mark Class A		



FCC Part 15, Class A
CISPR 22 Class A

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-chih, Taipei Hsien, Taiwan.
Tel: 886-2-2698-3878
Fax: 886-2-2698-3873
E-mail: kti@ktinet.com.tw
URL: http://www.ktinet.com.tw

KTI Networks Inc.

10415-A Westpark Drive, Houston,
TX 77042. U.S.A.
Tel: 1-713-266-3891
Fax: 1-713-914-0555
E-mail: contact@ktinet.com
URL: http://www.ktinet.com

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

Ordering Informaton:

KS-116 Ver.D	16-Port 10/100 Workgroup Fast Ethernet Switches
KS-124 Ver.E	24-Port 10/100 Workgroup Fast Ethernet Switches