

Optional Slide-in Modules for KS-2601

Doc.070928

KS-2601-8T

8-Port 100Base-TX slide-in module

- 8 x Shielded RJ-45
- Supports 10/100Mbps, full/half-duplex, auto-negotiation, auto-crossover, flow control functions
- Network cable: Cat.5 UTP

KS-2601-8MC

8-Port 100Base-FX SC slide-in module (Multimode)

- 8 x duplex SC
- Supports 100Mbps, full –duplex, flow control functions
- Network cable: MMF (Multimode Fiber)

KS-2601-8MT

8-Port 100Base-FX ST slide-in module (Multimode)

- 8 x ST
- Supports 100Mbps, full –duplex, flow control functions
- Network cable: MMF (Multimode Fiber)

KS-2601-8JM

8-Port 100Base-FX MT-RJ slide-in module (Multimode)

- 8 x MT-RJ
- Supports 100Mbps, full –duplex, flow control functions
- Network cable: MMF (Multimode Fiber)

KS-2601-8SL2

8-Port 100Base-FX SC slide-in module (SMF 20km)

- 8 x duplex SC
- Supports 100Mbps, full –duplex, flow control functions
- Network cable: SMF (Single Mode Fiber) up to 20km

KS-2601-8W3520-A

8-Port 100Base-FX Bi-Di SC slide-in module

- 8 x Bi-Di SC (Wavelength Tx 1310nm, Rx 1550nm)
- Supports 100Mbps, full –duplex, flow control functions
- Network cable: single SMF (Single Mode Fiber) up to 20km

KS-2601-8W5320-A

8-Port 100Base-FX Bi-Di SC slide-in module

- 8 x Bi-Di SC (Wavelength Tx 1550nm, Rx 1310nm)

- Supports 100Mbps, full –duplex, flow control functions
- Network cable: single SMF (Single Mode Fiber) up to 20km

KS-2601-1SX

1-Port 1000Base-SX slide-in module (Multimode)

- Duplex SC
- Supports 1000Mbps, full –duplex, flow control functions
- Network cable: MMF

KS-2601-1LX

1-Port 1000Base-LX slide-in module (Single Mode)

- Duplex SC
- Supports 1000Mbps, full –duplex, flow control functions
- Network cable: SMF

KS-2601-1GT

1-Port 1000Base-T slide-in module (Copper)

- Shielded RJ-45
- Supports 10/100/1000Mbps, full/half-duplex, auto-negotiation, auto-crossover, flow control functions
- Network cable: Cat.5e or better UTP

Optical Specifications

Module	Connector	Cable	Wavelength	Tx Power	Rx Sensitivity	Distance
KS-2601-8MC	Duplex SC	MMF	1310nm	-19 ~ -14dBm	-31dBm	2km
KS-2601-8MT	Duplex ST	MMF	1310nm	-19 ~ -14dBm	-31dBm	2km
KS-2601-8JM	Duplex MT-RJ	MMF	1310nm	-19 ~ -14dBm	-31dBm	2km
KS-2601-8SL2	Duplex SC	SMF	1310nm	-15 ~ -7dBm	-32dBm	20km
KS-2601-8W3520-A	Bi-Di SC	SMF	Tx 1310nm Rx 1550nm	-14 ~ -8dBm	-31dBm	15-20km
KS-2601-8W5320-A	Bi-Di SC	SMF	Tx 1550nm Rx 1310nm	-14 ~ -8dBm	-31dBm	15-20km

Module	Connector	Cable	Wavelength	Tx Power	Rx Sensitivity	Distance
KS-2601-1SX	Duplex SC	MMF 62.5/125	850nm	-15 ~ -7dBm	-32dBm	200m
		MMF 50/125				500m
KS-2601-1LX	Duplex SC	MMF 62.5/125	1310nm	-11 ~ -3dBm	-22dBm	550m
		MMF 50/125				550m
		SMF 9/125				10km